



GENERAL SPECIFICATIONS

• Overall Length (L.O.A)	13,94 m	45'9"
• Hull length	13,50 m	44'3"
• L.W.L.	12,98 m	42'7"
• Hull Beam	4,50 m	14'9"
• Deep draft	2,27 m	7'5"
• Deep ballast weight	2 808 kg	6,191 lbs
• Shallow draft	1,75 m	5'9"
• Shallow ballast weight	3 036 kg	6,693 lbs
• Air draft	20,60 m	67'7"
• Air draft (ICW)	19,35 m	63'6"
• Light displacement	10 549 kg	23,257 lbs
• Fuel tank capacity	200 L	53 US Gal
• Fresh water capacity (standard)	370 L	98 US Gal
• Fresh water capacity (Optional equipment)	200 L	53 US Gal
• Engine power	54 HP	54 HP
	POD 90	POD 90

ARCHITECT / DESIGNERS

- Naval Architect: Finot - Conq And associs
- Interior design: Nauta Design

CE CERTIFICATION

- Category A - 10 people
- Category B - 11 people
- Category C - 12 people

STANDARD SAIL LAYOUT AND AREA

• Mainsail (classic)	50,00 m ²	538 sq ft
• Genoa (104 %)	50,00 m ²	538 sq ft
• Asymmetrical spinnaker	156,00 m ²	1,679 sq ft
• I	17,43 m	57'2"
• J	5,65 m	18'6"
• P	16,36 m	53'8"
• E	5,43 m	17'10"



2 cabins - 2 head compartments



3 cabins - 2 head compartments



STANDARD EQUIPMENT

CONSTRUCTION

Design made following European Directive requirements and according to EC certification

- Monolithic hull in polyester
- Monolithic structural hull liner bonded to the hull
- Injection molded deck in glass fiber/balsa sandwich, covered with «diamond-point» non-slip coating
- Hull-deck joint screwed, bonded and trimmed with 1 toerail
- Cast iron keel fixed with bolts and stainless steel backing plates
- Rudder hung with glass compound stock
- White colored hull - Grey metal hull decoration

DECK EQUIPMENT

RIGGING

- Standard mast 9/10 anodized aluminum installed on the deck, 2 sets of spreaders
- Anodized aluminum boom
- Discontinuous stainless steel standing rigging
- 2 Backstays with turnbuckles
- Rigid boom vang
- Genoa furling system with drum on the deck
- 2 Stand Up blocks on mainsheet arch
- 2 Genoa tracks with piston adjusted traveller cars
- 2 Genoa sheet return blocks
- Rigging run back to cockpit (except boom topping lift)
- Complete running rigging: Main halyard, Genoa halyard with clutch on mast and cleat, Boom topping lift with cleat on mast, Mainsheet, 2 Genoa sheets
- 2 Reefing lines, 1 Manual reef
- 7 Line stoppers
- 2 Halyard bags

WINCHES

- 2 Self-tailing genoa sheet winches (H50.2 STC)
- 2 Self tailing coachroof winches (H40.2 STC)
- 2 Aluminum winch handles Speed Grip
- 2 Winch handle holders

SAILS

- Furling genoa with UV protective strip
- Semi full batten written sail with slider and roller slider
- System: Lazy Jack System and Lazy bag in Natural color

MOORING -ANCHORING GEAR

- Self-bailing chain locker - Clench bolt - Hatch cover
- Single roller stainless steel bow fitting with offset roller
- 1 12 V - 1000 W Vertical electric windlass - Remote control
- 6 Aluminum mooring cleats - Stainless steel deck line protection

SAIL LOCKER

- Access through deck hatch T60
- Stainless steel ladder
- Cubby hole lockers

SAFETY ON DECK

- 1 Open stainless steel forward pulpit - Step
- 2 Stainless steel aft pushpits
- 1 Ring lifebuoy bracket
- 1 Outboard engine bracket
- Flag mounts welded on aft pushpit
- Double lifelines and stainless steel stanchions - Access to port and to starboard in lifelines

COCKPIT

- Self-bailing cockpit
- 2 Cockpit locker
- 2 Lockers in cockpit floor under helm's feet
- 1 Liferaft locker under helm seat, in cockpit bottom (0,80 m x 0,40 m x 0,58 m / 2'7" x 1'4" x 1'11")
- 1 Gas locker for bottle(s) under the port helm seat
- Natural solid wood slatted cockpit benches
- 2 Steering wheel consoles: Stainless steel steering wheels - 900 mm diameter - Leather covered - Steering gear at the helm station - Metal cable transmission system - Stainless steel handrail - Navigation instrument pod (optional instruments) - Glass holder
- 1 Deck plate for access to tiller system + Power supply access hatch
- 1 Emergency tiller
- 2 Steering compass on consoles
- Portside engine control and control panel
- Polyester cockpit table - 2 Flaps - Glove boxes - 2 Large storage space - 2 Stainless steel handrails - 12 V Power outlet - Lamp with shade
- 1 Cold water cockpit shower
- 1 Fixed composite arch - Built-in lighting
- 2 Hinged PMMA companionway doors - Sliding hatch made of PMMA

SWIM DECK / STERN DECK

- Fully opening transom, convertible into swim platform (2,85 m x 0,77 m / 9'4" x 2'6")
- Electrically controlled opening swim platform
- Natural solid wood decking on swim platform
- 1 Stainless steel swim/boarding ladder - Solid wood steps - Folding

INTERIOR

- Woodwork Alpi Mahogany
- Parquet type laminated floors
- Padding upholstery in salon and cabins (White)
- Fabric upholstery
- Marine mattresses in the cabins

COMPANIONWAY

Headroom: 2,00 m / 6'7"

- Wooden salon companionway with molded wood hanging steps with non-slip surface
- 2 Stainless steel handrails

SALON

Headroom: 1,97 m / 6'6"

- U-shaped salon bench - Double density foam
- Central seating on pantograph
- Salon table in 1 piece - Varnished wood top with inlay - Aluminum legs
- Mirror on bulkhead
- Cupboard units - Cubby hole lockers and storage along the hull - Storage under bench seats
- Cubbyholes with stainless steel beading
- 2 Panoramic deck house windows with concertina blinds
- 2 Hull portholes with curtain
- 2 Opening portholes on coaming in side windows
- 1 Opening deck hatch with shutter / Mosquito screen

CHART TABLE - PORTSIDE

- Sliding, can be configured with the armchairs - Placed against the forward bulkhead, against the galley or between the 2 mobile seats
- Table with flap - Molded wood beading
- Switch panel on bulkhead for access to electrical functions
- 1 Reading light



BENETEAU

General Equipment list - North America

GALLEY - PORTSIDE

Headroom: 2,00 m / 6'7"

- L-shaped kitchen
- Countertop of synthetic surfaces
- 1 Stainless steel sink 2 rectangular basins - 1 Mixer tap cold water / hot water, under pressure
- 1 Gas stove 2 burners - Stainless steel oven on gimbal mountings - Stainless steel protection handrail
- 1 85 L ice box / 22 US Gal, top opening
- 1 12 V 130 L refrigerator / 34 US Gal, front opening
- Fitted cupboards and closed cubbyholes (Shelving, Garbage bin)
- 1 Lower cupboard: 1 Drawer - 2 Shelves
- 1 Opening portlight with curtains in side windows in the coaming
- Storage space along the hull

STARBOARD AFT CABIN

Headroom: 1,96 m / 6'5"

- 1 Double bed (2,05 m x 1,50 m x 1,15 m / 6'9" x 4'11" x 3'9") - Marine mattress
- Access door to starboard aft washroom
- Cupboard units - Hanging locker - Closed cubbyholes
- Storage each side of bed
- 1 Hull portholes with curtain
- 1 Cockpit windows with curtains
- 1 Cockpit porthole with curtain
- 1 Flush deck hatch with shutter / Mosquito screen

STARBOARD AFT HEAD COMPARTMENT

Headroom: 1,88 m / 6'2"

- Access through salon and the starboard aft cabin
- Separate shower - 1 Mixing tap hot water / Cold water
- 1 Manual marine toilet
- 1 Rigid holding tank 80L / 21 US Gal
- Sink - 1 Mixing tap hot water / Cold water
- Washroom cabinet
- 2 Mirrors
- Toilet accessories
- Cupboard
- 1 Opening portlight with curtains in side windows in the coaming

Version 2 cabins

AFT-GALLEY (PORT AFT)

Access via galley

- Large storage area (Numerous cupboards, Shelves, Drawers)
- Access door to port cockpit locker
- 1 Flush deck hatch with shutter / Mosquito screen

Version 3 cabins

PORT AFT CABIN

Headroom: 1,96 m / 6'5"

- 1 Double bed (2,05 m x 1,50 m x 1,15 m / 6'9" x 4'11" x 3'9")
- Cupboard - Hanging locker - Closed cubbyholes
- Storage each side of bed
- 1 Hull porthole with curtain
- 1 Cockpit porthole with curtain
- 1 Flush deck hatch with shutter / Mosquito screen
- 1 Cockpit windows with curtains

FORWARD CABIN

Headroom: 1,89 m / 6'2"

- Central double bed (2,05 m x 1,50 m x 1,15 m / 6'9" x 4'11" x 3'9")
- Hanging lockers - Glove box - Cubby hole locker - Lower cupboard - Stowage under platform
- 3 Flush deck hatches with shutter / Mosquito screen
- 2 Hull portholes with curtain

STARBOARD FORWARD HEAD COMPARTMENT

Headroom: 1,85 m / 6'1"

- Access through forward cabin
- Manual marine toilet
- Moulded basin - Shower mixer tap hot / Cold water
- Separate shower - 1 Mixing tap hot water / Cold water
- 1 Mirror
- Washroom cabinet
- Toilet accessories
- Cupboard
- 1 Flush deck hatch with shutter / Mosquito screen

ENGINE

- Engine Yanmar Diesel 54 hp / 54 HP Sail Drive
- Engine control - Control panel in the port cockpit
- Engine compartment: Soundproofing foam - Ventilation: 1 air intake and 1 air outlet
- 1 Alternator 12 V / 125 Ah
- 1 Rotomoulded diesel tank 200 L / 53 US Gal (under port aft berth) - Electronic gauge - Low level alarm - 1 Deck filler
- Filters: Sea water - Diesel - Decanter
- Fixed three blade propeller
- 1 Engine access through companionway (opening with 2 gas pistons) - 2 Engine access through aft cabins

ELECTRICITY

- 12 V Circuit
- 2 Service batteries (110 Ah) - 1 Engine battery (110 Ah)
- 1 Load balancer
- 12 V Electrical panel (Fuses - Voltmeter - Water gauge - Fuel gauge - Battery warning - Fuel warning - Water warning)
- 1 12 V Power outlets
- Lighting: Overhead lights - Reading lights - White striplighting
- Navigation lights: 1 Forward and aft navigation lights - 1 Engine navigation light / Deck light forward of mast - 1 Mooring light on masthead
- Wire runs for options cables
- Full 115 V system (Interior power outlet 115 V - 25 Amp battery charger - Shore power socket)

PLUMBING

- 1 Rotomolded freshwater tank (330 L / 87 US Gal Forward cabin) - 1 Deck filler
- Waterpressure system - Expansion tank - Inline filter
- 40 L Electric water heater / 11 US Gal (engine run)
- 1 Rigid holding tank 80L / 21 US Gal
- Delayed shower draining and electric shower drain pumps
- 1 Electric bilge pump - 1 Manual bilge pump
- 1 Electric ice box drain pump

GAS

- 1 Gas bottle box in the cockpit (diameter 0,34 m x 0,53 m / 1'1" x 1'9")
- Regulator and solenoid



TRIM LEVEL

	ESSENTIAL	EXCLUSIVE
<ul style="list-style-type: none"> • B&G Electronic: Helm consoles to port and starboard - 1 T41 Graphic display • B&G Electronic: Sensor (Log, Speedometer, Temperature) • B&G Electronic: Wind Sensor (Windvane, Anemometer) • Cockpit shower hot/cold water • Hifi: Fusion + Interior speakers & Waterproof exterior speakers • LED interior lights • 60 Amp battery charger instead of 25 Amp charger • 2 110 Amp additional service batteries 	<ul style="list-style-type: none"> • • • • • • • • 	<ul style="list-style-type: none"> • • • • • • • •
<ul style="list-style-type: none"> • 1 Port electric coachroof winch - H46.2 STAECH • Galley: 12 V Refrigeration unit in icebox (Freezer) • Salon: Leather covered stainless steel handrails • Storage space(s) under the floor • Stainless steel beading for fenders in cockpit locker • Salon: Indirect light LED • LED: Navigation lights 		<ul style="list-style-type: none"> • • • • • • •

PACKS

ELECTRONIC B&G PACK

A Pack

- Steering consoles: 2 Zeus 7" multifonction touch screens (GPS, Chart plotter, Chart reader - Cartography Navionics Silver included)
- B&G V50 VHF, AIS receiver function + Wireless handset

B Pack

- Swivel base on reverse side of cockpit table
- Multifunction touchscreen B&G Zeus 12"(GPS, Chart plotter, Chart reader - Cartography Navionics Silver included)

PERFORMANCE PACK

- Performance Elvström Windward 300+ Sails
- German system (Two-way mainsheet at the helm station)

OPTIONAL EQUIPMENT

Navigation electronics: B&G

- Wifi interface
- 4G Radar
- Chart table: Zeus 7" wide additional multifunction screen
- WR10 Wireless autopilot remote control
- AIS 400
- Forward Scan Sensor (Forward underwater vision)

Rigging - Sails

- Anodized mast furling system with mainsail
- ICW Roller furling mast
- Asymmetrical spinnaker rigging + Code 0 Rigging
- Self-tacking jib hardware
- Code 0 on furler
- Self-tacking jib (replacing genoa)
- Self-tacking staysail with manual furling + Fixed forestay
- Additional bow roller + Stainless steel bobstay
- Releasable fore-stay chain-plate
- Backstays with turnbuckles (Adjustable)*
- Genoa sheet track leads adjustable from the cockpit
- 2 Flag halyards

* *Except on mast with in-mast furling*

Winches

- Electric genoa sheet winches - H46.2 STCEH / 50.2 STC

Hull - Deck

- White or Grey hull
- Solid wood slatted on cockpit bottom
- Solid wood slatted side decks
- Remote control electric transom
- Bow thruster
- Refrigerated ice-box in cockpit table (30 L / 8 US Gal) - Positive cold
- 3 folding blades propeller
- White composite steering wheels + White PVC protective covers
- Stainless steel arch with davits
- Mooring kit
- Mooring cleats on transom
- Cockpit windlass control with chain counter
- Shore freshwater supply
- Rub rail

Interior equipment

- Interior woodwork: Alpi satin light oak
 - Interior upholstery: Ultraleather Graphite or Ivory
 - Upholstery padding (Salon and Cabins): Taupe
 - Luxe folding salon table (double berth compatible)
 - TV Pre-wiring + Player Fusion (Bluetooth, USB, DVD, MP3), in the salon
 - 115 V Microwave oven
 - Beneteau branded foldable seat
 - Double berth in salon
 - Additional holding tank
 - Electric Quiet Flush head
 - Extra water tank 200 L / 53 US Gal
 - Galley: Sea water/fresh water foot pump
 - Mosquito screens
-
- 12 V / 115 V inverter - 2.000 VA
 - 7.5 kVA Generator
 - Fuel forced-air heating system
 - 115 V Air conditioning / 50 Hz

