





Lifting keel - Optional equipment: Cradle











General Equipment list (Provisional) - North America **GENERAL SPECIFICATIONS***

 Overall Length (L.O.A): 	10,45 m	34'3"
Hull length	9,97 m	32'9"
• L.W.L.	9,70 m	31'10"
Hull Beam	3,72 m	12'2"
 Light displacement: 	5 533 kg	12,195 lbs
Deep draft	1,85 m	6'1'
 Deep ballast weight 	1 559 kg	3,436 lbs
 Shallow draft 	1,45 m	4'9"
 Shallow ballast weight 	1 825 kg	4,022 lbs
Air draft	15,45 m	50'8"
 Lifting keel version draft 	1,15/2,30 m	3'9"/7'7"
 Lifting keel version ballast weight 	2 151 kg	4,741 lbs
 Fresh water capacity: 		
- standard	130 L	34 US Gal
- Optional equipment	200 L	53 US Gal
 Fuel tank capacity 	130 L	34 US Gal
Engine power	30 HP	30 HP

ARCHITECTS / DESIGNERS _____

- Naval Architect: Finot Conq
- Outside & interior design: Nauta Design

CE CERTIFICATION*

- Category A 6 people
 Category B 8 people
 Category C 10 people

STANDARD SAILS DIMENSIONS*_____

• Mainsail	27,50 m²	297 sq ft
 Furling mainsail 	23,00 m ²	248 sq ft
• Genoa (102 %)	26,72 m²	288 sq ft
 Asymmetrical spinnaker 	83,45 m²	898 sq ft
Code 0	50,9 m²	548 sq ft
 Self-tacking jib 	25,5 m²	274 sq ft
•	12,45 m	40'10"
• J	4,29 m	14'1'
• P	12,20 m	40'
• E	3,90 m	12'10"
	1	

* Provisional specifications, boat in process of certification



Oceanis 35.1

STANDARD EQUIPMENT

CONSTRUCTION

- Design made following European Directive requirements and according to CE certification
- Monolithic hull in polyester
- Monolithic structural hull liner bonded to the hull
 Deck injection constructed in glass fibre and Saerform foam sandwich,
- covered with "diamond-point" non-slip coating • Hull-deck joint screwed, bonded and trimmed with 1 toerail
- Cast iron keel fixed with bolts and stainless steel backing plates
- 2 Underhung rudders with stainless steel stock
- White hull Grey metal hull decoration

DECK EQUIPMENT

RIGGING

- Standard mast 9/10 anodized aluminum installed on the deck, 2 sets of spreaders
- Anodized aluminum boom
- Discontinuous stainless steel standing rigging
- 1 Backstay: Bridle
- Rigid boom vang
- Genoa furling system with drum on the deck
- 2 Genoa tracks with piston adjusted traveller cars
- 2 Genoa sheet returns stainless steel fairleads
- Rigging run back to cockpit (except boom topping lift)
- Complete running rigging: Main halyard, Genoa halyard with clutch on mast and cleat, Boom topping lift with cleat on mast, Mainsheet, 2 Genoa sheets, 2 Automatic reefing system lines
- 4 Clutches, 4 Jamming cleats
- Main sheet on bridle, with fixed points on the roof
- optional extra:
 - Fixed composite arch, with incorporated LED lighting
 2 Stand-up blocks for mainsail sheet

WINCHES

- · 2 Self-tailing genoa sheet winches (H40.2 STA)
- 1 Coach roof winch self tailing (H35.2 STA)
- 1 Aluminium "Speed Grip" winch handle, 1 Winch handle holder

SAILS

- · Furling genoa with UV protective strip
- Semi full batten logo mainsail with slider (Roller slides for fully battened mainsail)
- Lazy Jack System and Lazy bag in Natural color

MOORING - ANCHORING GEAR

- Self-bailing chain locker Clench bolt Hatch cover
- Single stem roller
- 6 Aluminum mooring cleats Stainless steel deck line protection

SAFETY ON DECK

- 1 Open stainless steel forward pulpit, 2 Stainless steel aft pushpits
- 1 Ring lifebuoy bracket
- Double lifelines and stainless steel stanchions
- Openings in guardrail to port and starboard
- Flag mounts welded on aft pushpit

General Equipment list (Provisional) - North America

COCKPIT

- Self-bailing cockpit
- 1 Cockpit locker
- 2 Lockers in cockpit bottom Side helm seats
- 1 Liferaft locker aft cockipt (0,95 m x 0,59 m x 0,36 m / 3'1" x 1'11" x 1'2")
- Natural solid wood slatted cockpit benches (1,50 m x 0,50 m / 4'11" x 1'8")
 2 Steering wheel consoles: Stainless steel steering wheels 800 mm
- diameter / 2'7" Leather covered Steering gear at the helm station Metal cable transmission system Stainless steel handrail Navigation instrument pod (optional instruments) Glass holder
- 2 Steering compass
- 2 Deck access points to tiller system
- 1 Emergency tiller
- Portside engine control and control panel
- 2 Hinged PMMA companionway doors Sliding hatch made of PMMA
- 1 Swimming ladder

SWIM DECK / STERN DECK (Exclusive Trim level)

- Fully opening transom, convertible into swim platform (2,60 m x 0,70 m / 8'6" x 2'4")
- Gas locker strut opening (manual), 1 Stainless steel integrated telescopic swimming ladder

INTERIOR

- Alpi Mahogany wood interior
- Parquet type laminated floors
- Fabric lined hull in salon and forecabin
- PVC Dolaro White or Commando Natural upholstery, Foam density 35 kg/ $\ensuremath{\text{m}}^3$
- · Marine mattresses in the cabins

COMPANIONWAY

Headroom: 1,85 m / 6'1"

- · GRP salon companionway steps are coated with non-slip surface
- 2 Leather covered stainless steel handrails

LONG GALLEY ON STARBOARD VERSION

HANGING LOCKER - PORTSIDE

• Beam: 50 cm / 1'8"

SALON - PORTSIDE

Headroom: 1,90 m / 6'3"

- L-shaped salon bench seat
- · Storage under bench seats
- · Salon table with one-piece wood top 2 feet
- High closed storage units
- Chart table (with opening top) Reading light
- Shelves with fiddles
- 1 Coachroof panoramic window with curtain
- 2 Hull portholes with curtain
- 1 Opening deck hatch with mosquito blind
- 1 Opening porthole in coaming
- 6 Overhead lights

FORWARD CABIN

Headroom: 1,80 m / 5'11"

- Central double bed (1,75 m x 2,00 m x 0,45 m / 5'9" x 6'7" x 1'6")
- 2 Hanging lockers
- Drawer under the bed
- 1 Opening deck hatch with fan, mosquito blind
- 2 Hull portholes with curtain



Oceanis 35.1

LENGTHWAYS GALLEY COUNTER - STARBOARD

Headroom: 1,90 m / 6'3"

- Laminated worktop Taupe
- 1 Stainless steel sink 1 Rectangular stainless steel basin 1 mixing tap hot/ cold water
- 1 2 Burner stainless steel gas cooktop on gimbaled mounts
- Unit (Drawer & Cupboard units)
- Front opening refrigerator (12 V 130 L / 34 US Gal)
- Cubby hole locker, Garbage bin
- 1 Coachroof panoramic window with curtain

2 cabin layout

STARBOARD AFT: Interior stowage space

Headroom: 1,75 m / 5'9"

Direct access from the salon

· Allows direct access to the cockpit locker

PORT AFT: 1 cabin

Headroom: 1,75 m / 5'9"

- Dimensions Berths: 1,73 m x 1,98 m / 5'8" x 6'6"
- 1 Overhead light, 2 Reading lights
- · Open shelving
- Padded upholstery along the hull
- 1 Wood hanging locker
- Deck house opening porthole

3 cabin layout Headroom: 1,75 m / 5'9"

- 2 Aft cabins
- Dimensions Berths: 1,45 m x 2,00 m / 4'9" x 6'7"

AFT STARBOARD HEAD COMPARTMENT

Headroom: 1,90 m / 6'31"

- Access through salon
- 1 Sink, 1 Mixing tap hot/cold water, Shower
- 1 Manual marine toilet with 80 L / 21 US Gal rigid reserve
- Head cabinet, 1 Mirror, Toilet accessories, Hook
- 1 Overhead light
- 1 Opening portlight with curtains in side windows in the coaming

L-SHAPED GALLEY ON PORT SIDE VERSION

- Replacing the hanging locker and the chart table
- Galley with 100 L / 26 US Gal cool box instead of the 130 L / 34 US Gal fridge
- Full hull width salon: Bench seat on port and starboard sides, Large salon table with 2 leaves and bottle rack, Retractable chart table on starboard side

General Equipment list (Provisional) - North America

- Engine Yanmar Diesel 30 hp / 30 HP Sail Drive
- Engine control Control panel in cockpit
- Engine compartment: Soundproofing foam Ventilation: 2 air intakes and 1
 powered air expulsion
- 1 Alternator 12 V / 125 Amp
- 1 Rotomoulded diesel tank 130 L / 34 US Gal Gauge at the chart table 1 Deck filler
- Filters: Sea water Diesel Water separator
- Fixed three blade propeller
- 1 Engine access through companionway 3 access to engine by the sides of the companionway

ELECTRICITY

- 12 V Circuit
- 1 Service battery (80 Amp) 1 Engine battery (80 Amp)
- 1 Load balancer
 - 12 V electrical panel
 - 1 12 V Power outlet
- LED navigation lights: 1 Navigation light 1 Steaming light for motoring 1
 Mooring light on masthead
- Wire runs for options cables

PLUMBING

- 1 Rotomolded freshwater tank (130 L / 34 US Gal)
- 1 Deck filler
- Water unit
- 1 80 L / 21 US Gal Rigid holding tank
- Electric pump & Shower draining
- Water heater (25 L / 7 US Gal) engine run (110 V)

GAS

- Gas cylinder locker starboard aft cockpit (25 cm x 27 cm x 40 cm / 10" x 11" x 15")
- · Regulator and solonoid



TRIM LEVEL

Oceanis 35.1

General Equipment list (Provisional) - North America

	ESSENTIAL	EXCLUSIVE
B&G Electronic: 1 Triton 2 Graphic display (To port steering console)		
 B&G Electronic: Sensor (Log, Speedometer, Temperature) 		
Wind Sensor B&G (Windvane, Anenometer)		
Windex Windvane		
Cockpit shower hot/cold water		
1000 W Electric windlass - Remote control		
 Hifi: Fusion + Interior speakers & Waterproof exterior speakers 		
 Full 12/110 V system (Inside sockets, 40 Amp battery charger, Shore power socket) 		
2 80 Amp additional service batteries		
Solid wood slatted aft swim platform		
Solid wood helmsman grid seats		
• 2 Halyard bags		
LED indirect lighting in salon		-

PACKS

ELECTRONIC 2017 PACK, B&G

- 1 7" screen To port steering console (Triton 2 pass to starboard)
- B&G V50 VHF + Wireless handset
- Wifi module

PERFORMANCE PACK

- Performance Sails
- German System (Two-way mainsheet at the helm station)



Oceanis 35.1

OPTIONS

B&G Electronic

- B&G AC42 Autopilot + Control at steering station
- AIS 400
- ForwardScan Sensor (Forward underwater vision)

Rigging - Sails

- · Anodized mast furling system with Mylar Taffetas mainsail
- Asymmetrical spinnaker rigging + Code 0 rigging + 2nd bow roller and Bobstay
- Self-tacking jib hardware
- Code 0 on furler
- Self-tacking jib (replacing genoa)
- Asymmetrical spinnaker
- Backstay adjustment (Except on mast with in-mast furling)
- Genoa sheet track leads adjustable from the cockpit
- 2 Flag halyards

Winches

- Electric genoa sheet winch (H40.2 STAEH), instead of standard
- Port electric coachroof winch (H40.2 STAEH), instead of standard
- Coach roof winch to starboard manual (H35.2STA) + Clutches

Hull - Deck - Cockpit

- · Ballasted boat version Centreboard cast iron
- Pearl Grey hull
- Mainsail arch
- Solid wood slatted side decks
- Solid wood decking on cockpit sole
- "Luxe" cockpit table
- PVC cover White ("Luxe" cockpit table)
- Fixed cockpit windows in aft cabin(s)
- Cockpit opening porthole for aft cabin(s)
- Bimini Luxe, Cadet Grey
- Bimini Luxe + Sprayhood, Cadet Grey
- Dark Narval Cockpit cushions
- Inflatable gangway
- Inflatable swimming pool
- Pump for tender or inflatable structure (12 V)
- Bow thruster
- 3 blade folding propeller
- Windlass control with chain counter in cockpit (fixed)
- Shore freshwater supply
- Outboard engine bracket (Pushpit)
- Rub rail

General Equipment list (Provisional) - North America

Interior equipment

- Interior woodwork: Alpi Blond Oak
- Salon table extension (for lengthways galley counter)
- 1 Additional stool in salon
- Interior upholstery: Chine Moka, PVC Taupe
 - Upholstery padding (Salon and Cabins): Anthracite Grey or Taupe
- Pre-wiring for 19" TV in the salon, DVD Player, MP3
- Stainless steel 2 burner oven/grill cooker on mounting (instead of standard)
- Microwave
- Slatted bed base
- Double berth in salon (+ 1 Stool)
- Wood companionway stepsSeparate shower:
- Separate snower
 2 cabin layout



- Electric Quiet Flush head
- Additional freshwater supply tank (200 L / 53 US Gal)
- Sea water foot pump
- Mosquito screens
- Additional 40 L / 11 US Gal cool box (for L-shaped kitchen)
- Diesel heater "air pulse"
- Air conditioning
- Generator (for 2 cabin layout, only)
- 12V inverter

BENETEAU AMERICA – 105 Eastern Avenue, suite 201 - Annapolis, MD 21403 - USA www.beneteauamerica.com 07/26/2016 Code Beneteau V12665 (A) US Descriptions, illustrations, etc are provided only for your guidance. Our models may undergo some standard modifications or improvements without notice