













General Equipment list (Provisional) - North America **GENERAL SPECIFICATIONS***

 Overall Length (L.O.A) 	11,50 m	37'9"
Hull length	11,13 m	36'6"
• L.W.L.	10,72 m	35'2"
Hull Beam	3,99 m	13'1"
 Light displacement 	6 850 kg	15,102 lbs
Deep draft	2,08 m	6'10'
 Deep ballast weight 	1 790 kg	3,946 lbs
 Shallow draft 	1,64 m	5'5"
 Shallow ballast weight 	2 060 kg	4,542 lbs
Air draft	16,55 m	54'4"
 Fresh water capacity: 		
- standard	130 L	34 US Gal
 Optional equipment 	200 L	53 US Gal
 Fuel tank capacity 	130 L	34 US Gal
Engine power	30 HP	30 HP
	I	

ARCHITECTS / DESIGNERS _____

- Naval Architect: Finot Conq
- Outside & interior design: Nauta Design

CE CERTIFICATION*

- Category A 8 people
 Category B 9 people
- Category C 10 people

STANDARD SAILS DIMENSIONS*_____

 Mainsail 	32,70 m²	393 sq ft
 Furling mainsail 	30,00 m²	323 sq ft
• Genoa (103 %)	33,00 m²	355 sq ft
 Asymmetrical spinnaker 	114 m²	1,227 sq ft
Code 0	65 m²	700 sq ft
 Self-tacking jib 	25 m²	269 sq ft
• 1	14,01 m	46'
• J	4,79 m	15'9"
• P	13,25 m	43'6"
• E	4,21 m	13'10"

* Provisional specifications, boat in process of certification



STANDARD EQUIPMENT

CONSTRUCTION

- Design made following European Directive requirements and according to CE certification
- Monolithic hull in polyester
- Monolithic structural hull liner bonded to the hull
 Deck injection constructed in glass fibre and Saerform foam sandwich, covered with "diamond-point" non-slip coating
- Hull-deck joint screwed, bonded and trimmed with 1 toerail
- Cast iron keel fixed with bolts and stainless steel backing plates
- 2 Underhung rudders with stainless steel stock
- White hull Grey metal hull decoration

DECK EQUIPMENT

RIGGING

- Standard mast 9/10 anodized aluminum installed on the deck, 2 sets of spreaders
- Anodized aluminum boom
- Discontinuous stainless steel standing rigging
- 1 Backstay: Bridle
- Rigid boom vang
- Genoa furling system with drum on the deck
- 2 Genoa tracks with piston adjusted traveller cars
- 2 Genoa sheet returns stainless steel fairleads
- Rigging run back to cockpit (except boom topping lift)
- Complete running rigging: Main halyard, Genoa halyard with clutch on mast and cleat, Boom topping lift with cleat on mast, Mainsheet, 2 Genoa sheets, 2 Automatic reefing system lines
- 4 Clutches, 4 Jamming cleats
- Main sheet on bridle, with fixed points on the roof
- optional extra:
 - Fixed composite arch, with incorporated LED lighting
 2 Stand-up blocks for mainsail sheet

WINCHES

- · 2 Self-tailing genoa sheet winches (H40.2 STA)
- 1 Coach roof winch self tailing (H35.2 STA)
- 1 Aluminium "Speed Grip" winch handle, 1 Winch handle holder

SAILS

- · Furling genoa with UV protective strip
- Semi full batten logo mainsail with slider (Roller slides for fully battened mainsail)
- · Lazy Jack System and Lazy bag in Natural color

MOORING - ANCHORING GEAR

- Self-bailing chain locker Clench bolt Hatch cover
- Single stem roller
- 6 Aluminum mooring cleats Stainless steel deck line protection

SAFETY ON DECK

• 1 Open stainless steel forward pulpit, 2 Stainless steel aft pushpits

July 26, 2016 - (non-binding document)

- 1 Ring lifebuoy bracket
- Double lifelines and stainless steel stanchions
- Openings in guardrail to port and starboard
- Flag mounts welded on aft pushpit

General Equipment list (Provisional) - North America

COCKPIT

- Self-bailing cockpit
- 1 Cockpit locker
- 2 Lockers in cockpit bottom Side helm seats
- 1 Liferaft locker aft cockipt (0,95 m x 0,59 m x 0,36 m / 3'1" x 1'11" x 1'2")
- Natural solid wood slatted cockpit benches (1,69 m x 0,50 m / 5'7" x 1'8")
- 2 Steering wheel consoles: Stainless steel steering wheels 800 mm diameter / 2'7" - Leather covered - Steering gear at the helm station - Metal cable transmission system - Stainless steel handrail - Navigation instrument pod (optional instruments) - Cup holders
- 2 Steering compass
- 2 Deck access points to tiller system
- 1 Emergency tiller
- Portside engine control and control panel
- 2 Hinged PMMA companionway doors Sliding hatch made of PMMA
- 1 Swimming ladder

SWIM DECK / STERN DECK (Exclusive Trim level)

- Fully opening transom, convertible into swim platform (2,60 m x 0,70 m / 8'6" x 2'4")
- Gas locker strut opening (manual), 1 Stainless steel integrated telescopic swimming ladder

INTERIOR

- Alpi Mahogany wood interior
- Parquet type laminated floors
- Fabric lined hull in salon and forecabin
- PVC Dolaro White or Commando Natural upholstery, Foam density 35 kg/ m³
- · Marine mattresses in the cabins

COMPANIONWAY

Headroom: 1,96 m / 6'5'

- · GRP salon companionway steps are coated with non-slip surface
- 2 Leather covered stainless steel handrails

LONG GALLEY ON STARBOARD VERSION

LARGE HANGING LOCKER - PORTSIDE

Headroom: 1,85 m / 6'1'

- Beam: 70 cm / 2'4"
- 1 Overhead light
- 1 Opening porthole in coaming
- optional extra: Separate shower instead of this hanging locker

SALON - PORTSIDE

Headroom: 1,95 m / 6'5"

- L-shaped salon bench seat
- · Storage under bench seats
- Salon table with one-piece wood top 2 feet
- High closed storage units (port and starboard)
- Chart table (with opening top) Reading light
- Shelves with fiddles
- 1 Coachroof panoramic window with curtain
- 2 Hull portholes with curtain
- 1 Opening deck hatch with mosquito blind
- 1 Opening porthole in coaming
 Course to a literate to a literat
- 6 Overhead lights

FORWARD CABIN

· 4 Reading lights

Headroom: 1,95 m / 6'5"

- Double access door
- Central double bed (1,50 m x 2,08 m x 1,08 m / 4'11" x 6'10" x 3'7")

Code Beneteau V12675 (A) US

- 1 Hanging locker (to starboard)
- 1 Cupboard with shelves (to port)
- Glove box Open shelving Drawer under the bed
- 1 Opening deck hatch with mosquito blind
 2 Hull portholes with curtain



LENGTHWAYS GALLEY COUNTER - STARBOARD

- Headroom: 1,97 m / 6'6'
- · Laminated worktop Taupe
- 1 Stainless steel sink 1 Rectangular stainless steel basin 1 mixing tap hot/cold water
- Front opening refrigerator (12 V 130 L / 34 US Gal)
- Cubby hole locker, Garbage bin
- Coachroof panoramic window with curtain
- Stainless steel 2 burner gas hob / oven on gimbal mounting
- Unit (Drawer & Cupboard units)

STARBOARD AFT: Interior stowage space

- Headroom: 1,85 m / 6'1"
- Direct access from the salon
- Allows direct access to the cockpit locker
- optional extra: Separate shower instead of this hanging locker

PORT AFT: 1 cabin

Headroom: 1,85 m / 6'1"

- Dimensions Berth : 1,65 m x 2,18 m x 2,05 m / 5'5" x 7'2" x 6'9"
- 1 Hanging locker
- 2 Reading lights
- 1 Overhead light
- Open shelving
- · Padded upholstery along the hull
- Deck house opening porthole
- 2 Aft cabins
- Dimensions Berths: 1,50 m x 2,00 m x 1,65 m / 4'11" x 5'5" x 6'7"

AFT STARBOARD HEAD COMPARTMENT

- Headroom: 1,89 m / 6'2"
- Access through salon
- 1 Sink, 1 Mixing tap hot/cold water, Shower
- 1 Manual marine toilet with 80 L / 21 US Gal rigid reserve
- Head cabinet, 1 Mirror, Toilet accessories, Hook
- 1 Overhead light
- 1 Opening portlight with curtains in side windows in the coaming

L-SHAPED GALLEY ON PORT SIDE VERSION

- Replacing the hanging locker and the chart table
- Galley with 100 L / 26 US Gal cool box instead of the 130 L / 34 US Gal fridge
- Full hull width salon: Bench seat on port and starboard sides, Large salon table with 2 leaves and bottle rack, Retractable chart table on starboard side

General Equipment list (Provisional) - North America

ENGINE

- Engine Yanmar Diesel 30 hp / 30 HP Sail Drive
- Engine control Control panel in cockpit
- Engine compartment: Soundproofing foam Ventilation: 2 air intakes and 1 powered air expulsion
- 1 Alternator 12 V / 125 Amp
- 1 Rotomoulded diesel tank 130 L / 34 US Gal Gauge at the chart table 1
 Deck filler
- Filters: Sea water Diesel Water separator
- Fixed three blade propeller
- 1 Engine access through companionway 3 access to engine by the sides of the companionway

ELECTRICITY

- 12 V Circuit
- 1 Service battery (80 Amp) 1 Engine battery (80 Amp)
- 1 Load balancer
- 12 V electrical panel
- 1 12 V Power outlet
- LED navigation lights: 1 Navigation light 1 Steaming light for motoring 1 Mooring light on masthead
- Wire runs for options cables

PLUMBING

- 1 Rotomolded freshwater tank (130 L / 34 US Gal)
- 1 Deck fillerWater unit
- 1 Rigid 80 L / 21 US Gal black water holding tank for each WC
- Electric pump & Shower draining
- 1 Electric bilge pump & 1 Manual bilge pump
- Water heater (25 L / 7 US Gal) engine run (110 V)

GAS

 Gas cylinder locker - starboard aft cockpit (25 cm x 27 cm x 40 cm / 10" x 1" x 15") - Regulator and solonoid



TRIM LEVEL

General Equipment list (Provisional) - North America

	ESSENTIAL	EXCLUSIVE
B&G Electronic: 1 Triton 2 Graphic display (To port steering console)		•
 B&G Electronic: Sensor (Log, Speedometer, Temperature) 		
Wind Sensor B&G (Windvane, Anenometer)		
Windex Windvane		
Cockpit shower hot/cold water		
1000 W Electric windlass - Remote control		
 Hifi: Fusion + Interior speakers & Waterproof exterior speakers 		
 Full 12/110 V system (Inside sockets, 40 Amp battery charger, Shore power socket) 		
2 80 Amp additional service batteries		
Solid wood slatted aft swim platform		
Solid wood helmsman grid seats		
2 Halyard bags		
LED indirect lighting in salon		-

PACKS

ELECTRONIC 2017 PACK, B&G

- 1 7" screen To port steering console (Triton 2 pass to starboard)
- B&G V50 VHF + Wireless handset
- Wifi module

PERFORMANCE PACK

- Performance Sails
- German System (Two-way mainsheet at the helm station)



OPTIONS _

B&G Electronic 4G Radar

- B&G AC42 Autopilot + Control at steering station
- AIS 400
- · ForwardScan Sensor (Forward underwater vision)

Rigging - Sails

- · Anodized mast furling system with Mylar Taffetas mainsail
- Asymmetrical spinnaker rigging + Code 0 rigging + 2nd bow roller and
- Bobstav
- · Self-tacking jib hardware
- Code 0 on furler
- · Self-tacking jib (replacing genoa)
- Asymmetrical spinnaker
- · Backstay adjustment (Except on mast with in-mast furling) · Genoa sheet track leads adjustable from the cockpit
- Removable forestay + Tackle
- Chain plate (Removable forestay)
- · 2 Flag halyards

Winches

- · Electric genoa sheet winch (H40.2 STAEH), instead of standard
- · Port electric coachroof winch (H40 STAEH), instead of standard
- · Coach roof winch to starboard manual (H35.2 STA) + Clutches, instead of standard + Winch handle

Hull - Deck - Cockpit

- · Pearl Grey hull
- Mainsail arch
- · Solid wood slatted side decks
- · Solid wood decking on cockpit sole
- "Luxe" cockpit table • White PVC covers ("Luxe" cockpit table)
- · White PVC console covers
- Fixed cockpit windows in aft cabin(s)
- Cockpit opening porthole for aft cabin(s)
- Bimini Luxe + Sprayhood, Cadet Grey
- Bimini Luxe, Cadet Grey
- Dark Narval Cockpit cushions
- Pump for tender or inflatable structure (12 V)
- · Bow thruster
- 3 blade folding propeller
- · Windlass control with chain counter in cockpit (fixed)
- Shore freshwater supply
- Outboard engine bracket (Pushpit)
- · Complete mooring/anchoring kit
- Rub rail

General Equipment list (Provisional) - North America

- Interior equipment
- Interior woodwork: Alpi Blond Oak
- Salon table extension (for lengthways galley counter) •
- 1 Additional stool in salon
- Interior upholstery: Chine Moka, PVC Taupe
- Upholstery padding (Salon and Cabins): Anthracite Grey or Taupe •
- Pre-wiring for 19" TV in the salon, DVD Player, MP3 Stainless steel 2 burner oven/grill cooker on mounting
- Microwave
- Slatted bed base
- Double berth in salon (+ 1 Stool)
- Wood companionway steps
- Separate shower:
- 2 cabin layout



- 3 cabin layout



- · Electric Quiet Flush head
- Additional freshwater supply tank (200 L / 53 US Gal)
- Sea water foot pump
- · Mosquito screens
- Additional 40 L / 11 US Gal cool box (for L-shaped kitchen)
- · Diesel heater "air pulse"
- Air conditioning
- Generator (for 2 cabin layout, only)
- 12V inverter

BENETEAU AMERICA – 105 Eastern Avenue, suite 201 - Annapolis, MD 21403 - USA www.beneteauamerica.com 07/26/2016 Code Beneteau V12675 (A) US Descriptions, illustrations, etc are provided only for your guidance. Our models may undergo some standard modifications or improvements without notice